



## TWO/THREE-WHEELER TYRES



TWO/THREE-WHEELER TYRES



## NYLOGRIP ZAPPER FS

Features	Benefits
<ul style="list-style-type: none"> <li>• Front Fitment</li> <li>• Directional</li> <li>• Extended shoulders</li> <li>• Round profile</li> <li>• 'Sticky' compound</li> <li>• Unique tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Better stability</li> <li>• Sharp cornering capability</li> <li>• Good maneuverability</li> <li>• Good traction</li> <li>• Wet traction</li> </ul>

TYRE SIZE	PLY RATING / LOAD INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75-17	4PR / 41P	1.85	76	568	5.0	155@2.25	-	285	-	TR 19
2.75-18	42P	1.85	77	615	4.6	150@2.25	-	279	-	TR 29
90/90-17	49P	2.15	90	594	4.6	185@2.25	-	290	-	TR 29
2.50-18	4PR / 40L	1.6	65	596	50	140@2.3	-	282	-	A 29145



## NYLOGRIP FV

Features	Benefits
<ul style="list-style-type: none"> <li>• Rib Type</li> <li>• Extended shoulder</li> <li>• Reflective sides</li> </ul>	<ul style="list-style-type: none"> <li>• Better steering</li> <li>• Good for cornering</li> <li>• Aesthetics</li> <li>• Safety</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75-18	4PR / 44L	1.85	74	617	5.2	160@2.25	-	291	-	TR29/A29 1 45



## ZAPPER F



Features	Benefits
<ul style="list-style-type: none"> <li>• Centre rib</li> <li>• Extended shoulder</li> <li>• Superior compound</li> </ul>	<ul style="list-style-type: none"> <li>• Front Fitment</li> <li>• Superior cornering</li> <li>• Better road-grip</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75-18	42P	1.85	74	613	5.2	150@2.3	-	294	-	TR29/A29 1 45

## RIB



Features	Benefits
<ul style="list-style-type: none"> <li>• Front Fitment</li> <li>• Rib tread pattern</li> <li>• Front wheel design</li> </ul>	<ul style="list-style-type: none"> <li>• Fast cornering ability</li> <li>• Low rolling resistance</li> <li>• Good wet traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.50-16	4PR / 36L	1.5	65	545	5.1	125@2.25	-	265	-	TR 29
3.25-16	4PR / 48P	2.15	86	589	5.0	180@2.25	-	277	-	A 29145
2.75-18	4PR / 44L	1.85	75	614	5.2	160@2.25	-	299	-	TR 19
3.00-18	4PR	1.85	80	629	6.0	175@2.25	-	299	-	A29145
3.00-19	4PR / 49P	1.85	78	650	6.0	185@2.25	-	309	-	A29145
3.25-19	4PR / 54P	2.15	86	670	6.0	210@2.25	-	319	-	A 29145
2.50-18	4PR / 45L	1.6	69	597	5.9	140@2.25	-	282	-	TR /A29145



## NYLOGRIP ZAPPER

Features	Benefits
<ul style="list-style-type: none"> <li>• High performance compound</li> <li>• Rounded shoulder profile</li> <li>• Extended shoulder</li> <li>• Angle transverse grooves</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent mileage</li> <li>• Excellent grip while Cornering</li> <li>• Water channeling</li> </ul>

TYRE SIZE	PLY RATING / LOAD SPEED	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75-18	6PR / 48P	1.85	77	613	5.0	190@2.80	-	292.5	-	TR29
3.00-18	6PR / 52P	1.85	86	627	6.5	200@2.80	-	299.5	-	TR29
3.00-19	4PR / 49P	1.85	80	652	6.5	185@2.25	-	318	-	TR 29
3.25-16	6PR / 55P	2.15	88	587	6.5	180@2.25	-	298	-	TR 29 / A29145



## NYLOGRIP ZAPPER-Y

Features	Benefits
<ul style="list-style-type: none"> <li>• Riar Fitment</li> <li>• Extended shoulder</li> <li>• Round profile</li> <li>• 'Sticky' compound</li> <li>• Unique tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Sharp cornering capability</li> <li>• Good maneuverability</li> <li>• Good traction</li> <li>• Wet traction</li> </ul>

TYRE SIZE	LOAD SPEED / PR	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
80 / 90 - 18	45P	1.85	80	601	6.5	160@ 2.25	-	290	-	TR 29
90 / 90 - 18	51P	2.15	90	619	6.5	195@ 2.25	-	298	-	TR 29
100 / 90 - 18	56P	2.50	101	642	6.5	224@ 2.25	-	306	-	TR 29
130 / 90 - 15	66P	3.0	132	616	7.5	300@ 2.25	-	300	-	T4558
120 / 80-16	60P	2.75	114	606	6.7	250@ 2.25	-	295	-	TR 29
2.75 - 18	6PR/48P	1.85	76	616	5.5	190@ 2.80	-	300	-	TR 29
3.00 - 18	6PR/52P	1.85	81	628	6.8	200@ 2.80	-	305	-	TR 29
130/80-18	66P	2.15	114	672	7.3	333@2.3	-	318	-	TR 29



## ZAPPER C



Features	Benefits
<ul style="list-style-type: none"> <li>• High Performance Compund</li> <li>• Rounded &amp; extended shoulder profile</li> <li>• More cut-edges</li> <li>• Multiple cross over groove</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent traction</li> <li>• Better cornering</li> <li>• Superior wet braking</li> <li>• Better grip</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.00-18	6PR / 52P	1.85	86	631	7	200@2.8	-	297	-	A29145
100/90-17	55P	2.5	94	616	7.6	218@2.25	-	-	-	TR29
120/80-17	61P	2.75	124	632	7.3	257@2.3	-	-	-	TR29

## ZAPPER Q



Features	Benefits
<ul style="list-style-type: none"> <li>• High Performance Compund</li> <li>• Rounded &amp; Extended</li> <li>• Shoulder profile</li> <li>• Cross over groove</li> <li>• Decompression scope</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent Traction</li> <li>• Better Cornering</li> <li>• Better wet traction</li> <li>• Better wear</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
100/90-18	56P	2.5	96	646	7	224@2.3	-	306	-	TR 29
90/90-18	57P	2.15	88	622	7	230@2.8	-	298	-	TR 29
130/80-18	66P	3	129	665	7.2	300@2.3	-	318	-	TR 29
140/70-18	67P	3.75	135	662	7.3	307@2.3	-	-	-	TR 29
120/80-18	62P	2.75	107	666	7.2	265@2.3	-	311	-	TR29
110/90-18	61P	2.5	109	655	7.2	257@2.3	-	314	-	TR29
140/90-15	70P	3.5	142	633	7.4	335@2.3	-	-	-	T4558



## NYLOGRIP MOTO-D

Features	Benefits
<ul style="list-style-type: none"> <li>• Directional</li> <li>• Aggressive block design</li> <li>• Aggressive looks</li> </ul>	<ul style="list-style-type: none"> <li>• Better stability</li> <li>• Good traction on highway and off road conditions</li> <li>• Good wet traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.25-16	4PR / 48P	2.15	89	595	9.8	185@2.25	-	290	-	TR 29
2.50-17	6PR / 43L	1.6	65	568	5.4	155@2.80	-	275	-	TR 29
2.75-17	6PR / 49L	1.85	75	588	5.8	185@2.80	-	285	-	TR 29
2.75-18	6PR / 50L	1.85	73	618	7.0	190@2.80	-	300	-	TR 29
300-18	6PR / 52P	1.85	77	638	9.0	200@2.85	-	310	-	TR 29
2.25-19	6PR / 42L	1.5	62	607	4.4	145@2.75	-	295	-	TR 29
300-19	4PR / 49P	1.85	80	661	9.5	181@2.25	-	332	-	TR 29
2.25-16	6PR / 36L	1.5	61	535	5.5	125@2.85	-	-	-	A29145
2.50-16	6PR / 41L	1.5	65	547	6.3	145@2.85	-	256	-	A29145

## NYLOGRIP MOTO-C



Features	Benefits
<ul style="list-style-type: none"> <li>• Directional block pattern</li> <li>• Off-set blocks</li> <li>• Transverse groove</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent on / off application</li> <li>• Better ride</li> <li>• Superior grip</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75-18	6PR / 50L	1.6	72	619	7.2	190@2.8	-	291	-	TR 29/A29 1 45
300-18	6PR / 52P	1.85	79	635	9.1	200@2.8	-	297	-	A29145
4.25-18	66P	2.5	112	698	9.4	300@2.3	-	323.5	-	TR 29



## NYLOGRIP PLUS



Features	Benefits
<ul style="list-style-type: none"> <li>• Rear Fitment</li> <li>• Siped block design</li> <li>• Tread with centre groove</li> <li>• Flat centre design</li> <li>• Rounded shoulder</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent road grip</li> <li>• Water channeling</li> <li>• High mileage and good ride comfort</li> <li>• Excellent cornering Characteristics</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.25-16	4PR / 48P	2.15	86	592	8.5	180@2.25	-	279	-	TR29
3.00-18	6PR / 52P	1.85	81	627	8.5	175@2.25	-	298	-	TR29
3.50-18	4PR / 56P	2.15	95	657	9.5	225@2.25	-	311	-	TR29
3.00-19	4PR / 49P	1.85	82	656	8.5	185@2.25	-	313	-	TR29
3.25-19	4PR / 54P	2.15	87	672	8.5	210@2.25	-	321	-	TR29
3.50-19	4PR / 57P	2.15	95	683	9.5	230@2.25	-	327	-	TR29

## NYLOGRIP LAPPER



Features	Benefits
<ul style="list-style-type: none"> <li>• Both wheel fitment</li> <li>• Directional</li> <li>• Block design</li> <li>• Aggressive looks</li> </ul>	<ul style="list-style-type: none"> <li>• Better stability</li> <li>• Good traction on highway And off road conditions</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75 - 16	6PR / 48L	1.85	75	566	6.2	180 @ 2.8	-	265	-	TR 29
2.25- 17	4PR / 33L	1.60	62	564	4.8	115@ 2.25	-	275	-	TR 29
2.50 - 17	6PR / 43L	1.6	70	575	5.0	155@ 2.8	-	270	-	TR 29
2.75 - 17	6PR / 49L	1.85	75	595	5.8	185@ 2.8	-	278	-	TR 29

# TWO/THREE-WHEELER TYRES



## NYLOGRIP - ST

Features	Benefits
<ul style="list-style-type: none"> <li>• Fitment Both Wheel</li> <li>• Block design</li> </ul>	<ul style="list-style-type: none"> <li>• Optimum performance with aggressive look</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.00-17	4PR	1.20	55	548	4.0	85@1.80	-	262	-	A 29132
2.75-18	6PR	1.85	75	614	5.0	191@2.80	-	292	-	A29132
2.25-19	6PR / 42L	1.5	60	606	4.4	145@2.75	-	295	-	TR 29



## NYLOGRIP - ST PLUS

Features	Benefits
<ul style="list-style-type: none"> <li>• Both Wheel Fitment</li> <li>• Block design</li> </ul>	<ul style="list-style-type: none"> <li>• Optimum performance with aggressive look</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75-18	6PR / 50L	1.85	76	615	7.0	190@2.80	-	300	-	TR 29





## NYLOGRIP - TT



Features	Benefits
<ul style="list-style-type: none"> <li>• Both Wheel Fitment</li> <li>• Unique tread pattern with centre grooves and shoulder buttons</li> </ul>	<ul style="list-style-type: none"> <li>• Superior mileage coupled with excellent traction</li> <li>• Excellent cornering ability</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.25-16	6PR / 36L	1.60	61	534	4.5	125@2.8	-	254	-	A29145
2.50-16	6PR / 41L	1.60	65	544	5.0	145@2.8	-	257	-	A29145
2.25-17	4PR / 33L	1.60	60	560	4.0	115@2.25	-	264	-	A29145
2.25-17	6PR / 38L	1.60	60	560	4.0	132@2.8	-	267.5	-	A29145
2.50-17	6PR / 43L	1.6	70	575	5.0	155@2.8	-	270	-	A29145
2.75-17	6PR / 49L	1.85	77	590	5.0	186@2.8	-	281.5	-	A29145
2.25-17	6PR / 38L	1.60	60	560	5.5	132@2.8	-	264	-	A29145
2.75-17	6PR / 49L	1.85	77	590	5.4	185@2.8	-	278	-	A29145

## TRAIL



Features	Benefits
<ul style="list-style-type: none"> <li>• Trail Tyre</li> </ul>	<ul style="list-style-type: none"> <li>• Good off the road capability</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
2.75-18	4PR / 44L	1.85	79	635	9	150@2.25	-	292	-	TR29/A29 1 45
3.00-18	4PR	1.85	80	633	9	175@2.25	-	298	-	TR 29/A29 1 45

# TWO/THREE-WHEELER TYRES



## NYLOGRIP



Features	Benefits
<ul style="list-style-type: none"> <li>• Both Wheel Fitment</li> <li>• Block tread pattern with tie bars</li> </ul>	<ul style="list-style-type: none"> <li>• Aggressive block design with excellent road grip</li> <li>• Rigid tread elements for uniform tread wear</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.50-18	4PR / 56P	DIV.2.15	87	385	7.0	170@2.55	-	177	-	VI-08-3*
3.00-10	4PR / 42J	DIV.2.15	80	413	6.0	150@2.55	-	192	-	VI-08-1*
3.50-10	4PR / 51J	DIV.2.15	87	438	7.0	195@2.55	-	202	-	VI-08-1*

\*Select tube valves based on Vehicle Model.

## NYLOGRIP - PLUS



Features	Benefits
<ul style="list-style-type: none"> <li>• Both When Fitment</li> <li>• Block tread pattern with tie bars</li> </ul>	<ul style="list-style-type: none"> <li>• Aggressive block design with excellent road grip</li> <li>• Rigid tread elements for uniform tread wear</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.50-8	4PR / 46J	DIV.2.5C	92	386	8.0	170@2.55	-	174	-	VI-08-3*
3.50-10	4PR / 51J	DIV.2.5C	93	439	8.0	195@2.55	-	200	-	VI-08-1*

\*Select tube valves based on Vehicle Model.



## NYLOGRIP FE



Features	Benefits
<ul style="list-style-type: none"> <li>• Centre Groove</li> <li>• More circumferentially oriented groove</li> <li>• Extended shoulder</li> <li>• Channel groove</li> </ul>	<ul style="list-style-type: none"> <li>• Better steering response</li> <li>• Superior wear</li> <li>• Better cornering</li> <li>• wet traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
90/100-10	53J	2.1	92	440	7.2	195@2.55	-	2.02	TT	VI-08-1

## NYLOGRIP 001



Features	Benefits
<ul style="list-style-type: none"> <li>• Small button</li> <li>• Block tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Cushioned ride</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.50-10	4	2.1	92	440	7.4	195@2.55	-	202	-	VI-08-1
3.50-8	4	2.1	88	385	7.4	170@2.5	-	177	-	VI-08-3



## NYLOGRIP ZAPPER

Features	Benefits
<ul style="list-style-type: none"> <li>• Directional</li> <li>• Extended shoulders</li> <li>• Round profile</li> <li>• 'Sticky' compound</li> <li>• Unique tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Better stability</li> <li>• Sharp cornering capability</li> <li>• Good maneuverability</li> <li>• Good traction</li> <li>• Wet traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.50-8	4	Div. 2.5C	91	384	6.4	170@ 2.55	-	175	-	V1-08-3
3.50 -10	4	Div. 2.5C	92	437	6.4	195@ 2.55	-	202	-	V1-08-3
3.00 -10	4	Div. 2.1	80	413	5.8	150@ 2.55	-	192	-	V1-08-3



## ZAPPER FG

Features	Benefits
<ul style="list-style-type: none"> <li>• Directional</li> <li>• Extended shoulder</li> </ul>	<ul style="list-style-type: none"> <li>• Better wear</li> <li>• Excellent cornering</li> <li>• Good wet traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
90/90-12	54J	1.9*	90	468	5.8	212@2.5	-	220		V1-08-1

\* Available in Tubless



## ZAPPER D



Features	Benefits
<ul style="list-style-type: none"> <li>• Directional</li> <li>• Extended shoulder</li> <li>• Aggressive pattern wide center rib</li> </ul>	<ul style="list-style-type: none"> <li>• Better wear</li> <li>• Excellent cornering</li> <li>• Good wet traction For handling</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
100/90-10	56J	2.5*	103	435	6.8	224@2.55	-	201	-	V1-08-1
100/90-12	59J	1.9*	100	486	6.7	243@2.55	-	226	-	V1-08-1

\* Available in Tubless

## ZAPPER N



Features	Benefits
<ul style="list-style-type: none"> <li>• High performance compound</li> <li>• International styling</li> <li>• Rounded &amp; extended shoulder profile</li> <li>• Decompression scope</li> </ul>	<ul style="list-style-type: none"> <li>• Better traction</li> <li>• Excellent cornering</li> <li>• Better wear</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
130/70-12	56L	3.75*	127	497	6	195@2.35	-	227	-	V1-08-3
120/70-12	51L	3.75*	117	483	4.4	224@2.35	-	222	-	V1-08-3



## AUTOMILER

Features	Benefits
<ul style="list-style-type: none"> <li>• All Wheel</li> <li>• 5 rib tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent mileage</li> <li>• Firmer road grip</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.00-8	6	DIV.3.00D	115	423	9.0	400@4.35	-	192	-	VI-08-3



## NYLORICK

Features	Benefits
<ul style="list-style-type: none"> <li>• All Wheel</li> <li>• 3 rib tread pattern with blocks on shoulder</li> </ul>	<ul style="list-style-type: none"> <li>• Dependable mileage</li> <li>• Good traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.00-8	4	DIV.3.00D	111	416	7.5	340@3.50	-	188	-	VI-08-3



## TRIPLE PLUS



Features	Benefits
<ul style="list-style-type: none"> <li>• All Wheel fitment</li> <li>• 3 rib tread pattern with blocks on shoulder</li> </ul>	<ul style="list-style-type: none"> <li>• Dependable mileage</li> <li>• Good traction</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.00-8	6	DIV.3.00D	111	421	7.8	400@4.35	-	192	-	VI-08-3
4.50-10	8	DIV.3.50D	121	497	10.0	520@4.35	-	233.8	-	TR 13

## SAVARI



Features	Benefits
<ul style="list-style-type: none"> <li>• All Wheel fitment</li> <li>• Higher land to sea ratio</li> <li>• 5 Rib tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent Milage</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.00-8	6	2.8	115	429	9.2	400@4.33	-	195.5	-	V1-08-3
4.50-10	8	2.7	119	494	10.1	500@5.00	-	231.5	-	TR13



## SAVARI TREK



Features	Benefits
<ul style="list-style-type: none"> <li>• Rib / Lug patterns</li> <li>• Open &amp; aggressive tread design</li> <li>• premium tread compound</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent traction</li> <li>• Enhanced mileage</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.50-10	8	2.7	119	496	10.8	500@5		235.3		TR13

## SAVARI LUG



Features	Benefits
<ul style="list-style-type: none"> <li>• Lug pattern</li> <li>• Premium tread compound</li> </ul>	<ul style="list-style-type: none"> <li>• Excellent traction</li> <li>• Excellent mileage</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.00-8	6	3	112	427	8.0	400@4.33	-	-	-	V1-08-3
5.00-10	8	3.5	148	523	11.0	580@4.6	-	-	-	TR13